



MULTIPURPOSE GREASE

LITOL-24



Description

Universal anti-friction waterproof lithium grease for application in the units of friction of caterpillar and wheeled transport vehicles, industrial equipment and ship mechanisms of the different setting.

Advantages







Multipurpose grease Litol-24 has the followings advantages:

- high colloid, chemical and mechanical stability;
- good preservation properties;
- use in the closed units (wheel hubs of cars, bearings of aquatic pumps and other) instead of general purpose grease;
- increasing of period between the leadthrough of regulation lubricating works;
- universal multipurpose grease for greasing all kinds of friction units.

Accordance

Multipurpose grease Litol-24 corresponds to classes: NLGI 3

Packaging types


0,375 kg		0,375 kg	
4,5 kg		9 kg	
17,5 kg		170 kg	

Typical descriptions

Melting point, °C	198
Penetration at 25°C, $\times 10^{-1}$ mm	245
Breaking point at 20°C, Pa	700
Colloidal constancy, %	11
Vaporability at 120°C, %	3,0



Technical oils plant "JV YUKOIL".
3A, Bazova str., Zaporozhzhya, 69084, Ukraine.
Phone: +38 061 717 11 40.

 Produced at GOST 21150-87.
This is reference data and can be changed without notification.
This publication from 01.01.2010 replaces all early the published descriptions of this product.