



TRANSMISSION OIL

# TAD-17i



## Description


Universal classic multigrade oil. Used for lubricating of all types of transmissions, including hypoid, trucks and automobile cars, minibuses.

## Advantages

Motor oil TAD-17i has the followings advantages:

- provides the high level of protecting from a wear in the wide range of loadings;
- low vaporability at high working temperatures;
- stably high workings descriptions at the different operation modes during the long-term period of time;
- possesses good antifoam and anticorrosive properties, compatibility with compression materials;
- on results of stand tests JSC «ZAZ» oil approve and recommend to use;
- the modern antiscoring additives package provides the high level of defence at the different loadings, including shock.

## Packaging types



## Accordance

Oil TAD-17i corresponds classes:

API GL-5 and SAE 85W-90.

## Типичные характеристики

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	18,5
Density at 20°C, kg/m <sup>3</sup>	893
Viscosity index	105
Alkali neutralization number, mg KOH/g	0,7
Flash point in open crucible, °C	230
Solidification temperature, °C	-25



Technical oils plant "JV YUKOIL".  
3A, Bazova str., Zaporozhzhya, 69084, Ukraine.  
Phone: +38 061 717 11 40.

**!** Produced at TU U 23.2-31852954-002-2003  
This is reference data and can be changed without notification.  
This publication from 01.01.2010 replaces all early the published descriptions of this product.