



TRANSMISSION OIL

# TM-3 80W-90



## Description


TM-3 80W-90 – multigrade transmission oil. Used for lubricating of cylindrical, bevel, helical-bevel and hypoid transmissions, in which contact tensions arrive to 2500 MPa and temperature of oil to 150°C in a volume.

## Advantages

Motor oil TM-3 80W-90 has the followings advantages:

- the modern antiscoring additives package provides the high level of defence at the different loadings, including shock;
- cost decreasing on operating costs and service;
- low vaporability at high working temperatures;
- possesses good antifoam and anticorrosive properties, compatibility with compression materials;
- control of quality provides the high level of operating descriptions oil.

## Packaging types



## Accordances

Oil TM-3 80W-90 corresponds classes:

API GL3 и SAE 80W-90

## Typical descriptions

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	15,6
Density at 20°C, kg/m <sup>3</sup>	900
Viscosity index	97
Flash point in open crucible, °C	230
Solidification temperature, °C	-25



Technical oils plant "JV YUKOIL".  
3A, Bazova str., Zaporozhzhya, 69084, Ukraine.  
Phone: +38 061 717 11 40.

**!** Produced at TU U 23.2-31852954-013-2003  
This is reference data and can be changed without notification.  
This publication from 01.01.2010 replaces all early the published descriptions of this product.