



TRANSMISSION OIL

TM-4 80W-90



Description


TM-4 80W-90 – universal multigrade transmission oil for trucks and passenger cars. Used for lubricating of cylindrical, bevel, helical-bevel and hypoid transmissions, in which contact tensions arrive to 3000 MPa and temperature of oil to 150°C in a volume .

Advantages

Transmission oil TM-4 80W-90 has the followings advantages:

- stably high workings descriptions at the different operation modes during the long-term period of time;
- possesses good antifoam and anticorrosive properties, compatibility with compression materials;
- provides the high level of protecting from a wear in the wide range of loadings;
- substantially reduces the wear of gearings and bearings;
- the modern antiscoring additives package provides the high level of defence at the different loadings, including shock.

Packaging types



Accordances

Oil TM-4 80W-90 corresponds classes:

API GL-4 и SAE 80W-90

Typical descriptions

Kinematic viscosity at 100°C, mm ² /s	15,0
Density at 20°C, kg/m ³	891
Viscosity index	10
Flash point in open crucible, °C	225
Solidification temperature, °C	-25



Technical oils plant "JV YUKOIL".
3A, Bazova str., Zaporozhzhya, 69084, Ukraine.
Phone: +38 061 717 11 40.

! Produced at TU U 23.2-31852954-013-2003
This is reference data and can be changed without notification.
This publication from 01.01.2010 replaces all early the published descriptions of this product.