

YUKO FENIX XHP2

HIGH-PREMIUM GREASE BASED ON CALCIUM SULFONATE AND SYNTHETIC COMPONENTS.

SPECIFICATIONS:

NLGI 2

DESCRIPTION:

It is recommended for application in roll stands mechanisms and drive gear axis of hot rolling steel mills, continuous casting machines; mechanisms and fittings for boilers, furnace and autoclaves; cement, chemical and glass industries equipment, operating under high temperatures.

The mechanisms and nodes of road-building machinery and heavy vehicles, vibrating screens of the asphalt plants, heavy loaded bearings in heavy industry; bearings for paper and pulp industry equipment, bearings and equipment components used for gas concrete production, drills and hammers; electric motor bearings of large dimensions.

BENEFITS:

- Ensures efficient lubrication, high thermal and antioxidant stability and low oil separation at high temperatures;
- Exceptional extreme pressure and anti-wear performance under heavy and shock loads;
- High resistance against corrosion, water and steam washout, destruction resistance under mechanical shifting forces and dirty water influence;
- Increased lubrication service intervals and reducing maintenance costs.

TYPICAL CHARACTERISTICS:

Thickening agent	calcium sulfonate complex
Penetration at +25° C , mm•10-1	270
Dropping point , °C	350
4 Ball test: Weld Point Test, H	4136
4 Ball test: Wear Test, mm	0,3

Packing	Vendor code	Barcode
Cartouche plastic 0.4l	017402	4820070246414
Bucket tin 17kg	011751	482007024476

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.