

TRANS HD 75-140

HIGH QUALITY SYNTHETIC OIL

SPECIFICATIONS:

SAE 75W-140 API GL-5

DESCRIPTION:

High quality synthetic oil for axles, gearboxes and heavy duty transmissions. Recommended for use in SCANIA axles when API GL-5 performance is required, in systems equipped with an oil filter.

BENEFITS:

- A high level of wear protection within a wide load range;
- Good lubrication and easy cold start including at low temperatures throughout the service life;
- Consistently high performance in various operating modes;
- Has increased oil drain period due to the high thermal stability.
- Excellent frictional properties ensure smooth gear change and quiet operation;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	24,0 – 32,5
Density at 20°C, kg/m ³	900
Viscosity index	175
Flash point in an open crucible, °C	200
Freezing point, °C, not higher	-40

Packing	Vendor code	Barcode
Canister plastic 20l	019942	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.