

1-13 (NLGI 3/4)

UNIVERSAL ANTI-FRICTION LUBRICANT.

SPECIFICATIONS:

NLGI 3/4

DESCRIPTION:

Intended for lubrication of various rolling bearings, less often - sliding, bearings of electric motors, wheel hubs of outdated models of cars. The service life of the lubricant in the bearings is quite long. In the bearings of electric motors, the lubricant is changed every three years. Supply of lubricant to the friction nodes is carried out both with the help of blowers and by the embedded method.

BENEFITS:

- Balanced recipe and high-quality raw materials;
- Long-service life in bearings;
- High pumping ability at low temperatures.

TYPICAL CHARACTERISTICS:

Efficient viscosity at 0 °C,	350
Tensile strength at 80 °C, Pa	200
Dropping point, °C	140
Colloid stability,%, not more	10
Evaporation	1,6
Penetration at 25 °C, mm×10 ⁻¹	220

Packing	Vendor code	Barcode
Bucket tin 17kg	009970	482007024452

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.